HOTEC

HAND DRYER

SENSOR OPERATED

JET



Reference: 11.101 white



Reference: 11.102 silver grey


COMPONENTS & MATERIALS

- ·High-impact ABS one-piece cover.
- ·High speed self-developed brushless motor.
- ·3 IR sensors in both sides for automatic hands detection.
- ·Filter which avoids the entry of the large particles.
- ·Internal tank to collect the water and avoid a mess.
- Designed for high traffic bathroom and continuous use.
- ·Easy maintenance.
- ·Dimension: 685 high x 300 wide x 220 deep mm.

TECHNICAL SPECIFICATIONS	
· Material	ABS
· Cover thickness	3.0 mm thick
· Voltage/Frequency	AC220V, 50/60Hz
· r.p.m.	20000
· Total power	1650-2050W
· Motor power	750W
· Heating element power	900-1300W
· Air velocity	95m/s
· Air temperature	20-40℃
· Noice level	72dB
· Protection level	IPX4
· Drying time	5-7s

CERTIFICATE

TECHNICAL DRAWING



220mm 2mm 101mm 300mm * 322222 * 32222X 46mm 270mm

Tel: +86 571 888 685 70

Fax: +86 571 888 685 71 hotec@cnhotec.com www.cnhotec.com