
## HOTEC

## HAND DRYER

SENSOR OPERATED

JET





Reference: 11.106



white	silver grey	
COMPONENTS & MATERIALS	TECHNICAL SPECIFICATIONS	
·High-impact ABS one-piece cover.	· Material	ABS
·High speed self-developed brushless motor.	· Cover thickness	3.0 mm thick
·1 IR sensors on the top for automatic hands	· Voltage/Frequency	AC220V, 50/60Hz
detection.	· Consumption	5.3-7.5A
·HEPA filter which avoids the entry of the tiny	· r.p.m.	11000-20000
particles.	· Total power	1000-1300W
·Internal tank to collect the water and avoid a mess.	· Motor power	450-750W
·Designed for high traffic bathroom and continuous	· Heating element power	550W
use.	· Air velocity	75-110m/s
·Easy maintenance.	· Air temperature	20-40°C
·Dimension: 615 high x 318 wide x 185 deep mm.	· Noice level	69dB
	· Protection level	IPX4
	· Drying time	7-10s
CERTIFICATE	TECHNICAL DRAWING	

Tel: +86 571 888 685 70

Fax: +86 571 888 685 71 hotec@cnhotec.com www.cnhotec.com

\_\_ 318mm

- 185mm -

615mm