HOTEC

HAND DRYER

SENSOR OPERATED

JET



Reference: 11.107

white



Reference: 11.108


silver grey

I	COI	V	P(7	IEN	ZTL	R	MA	TER	IALS
ı		VI.		<i>,</i>	ועוו	1 1 17	Œ			

- ·High-impact ABS one-piece cover.
- ·High speed brush motor.
- ·4 IR sensors in both sides for automatic hands detection.
- ·HEPA filter which avoids the entry of the tiny particles.
- ·Internal tank to collect the water and avoid a mess.
- Designed for high traffic bathroom and continuous use.
- ·Easy maintenance.
- ·Dimension: 699 high x 300 wide x 220 deep mm.

TECHNICAL SPECIFICATIONS					
· Material	ABS				
· Cover thickness	3.0 mm thick				
· Voltage/Frequency	AC220V, 50/60Hz				
· r.p.m.	20000				
· Total power	2000-2450W				
· Motor power	550W				
· Heating element power	1450-1900W				
· Air velocity	95m/s				
· Air temperature	20-40°C				
· Noice level	72dB				
· Protection level	IPX4				
· Drying time	7-9s				

CERTIFICATE



TECHNICAL DRAWING





Tel: +86 571 888 685 70 Fax: +86 571 888 685 71 hotec@cnhotec.com www.cnhotec.com