HOTEC

HAND DRYER

SENSOR OPERATED

JET



Reference: 11.111 white




Reference: 11.112 silver grey

- ·High-impact ABS one-piece cover.
- ·High speed self-developed brushless motor.
- ·3 IR sensors in both sides for automatic hands detection.
- ·HEPA filter which avoids the entry of the tiny particles.
- Internal tank to collect the water and avoid a mess.
- Designed for high traffic bathroom and continuous use.
- ·Easy maintenance.
- ·Dimension: 657 high x 289 wide x 203 deep mm.


| TECHNICAL SPECIFICATIONS | |
|--------------------------|-----------------|
| · Material | ABS |
| · Cover thickness | 3.0 mm thick |
| · Voltage/Frequency | AC220V, 50/60Hz |
| · r.p.m. | 21500 |
| · Total power | 1300-1800W |
| · Motor power | 500-700W |
| · Heating element power | 800-1100W |
| · Air velocity | 85-105m/s |
| · Air temperature | 25-40°C |
| · Noice level | 60dB |
| · Protection level | IPX4 |
| · Drying time | 5-10s |
| | |

CERTIFICATE





TECHNICAL DRAWING



Tel: +86 571 888 685 70

Fax: +86 571 888 685 71 hotec@cnhotec.com www.cnhotec.com